OWCdigital.com

Up to 540MB/s | Thunderbolt 3 | Bus Powered | Mac & PC

# OWC
# Mercury Elite Pro mini
USB 3.1 Gen 2 Type-C

**A Portable, Plug and Play Powerhouse**

Perfect for client meetings, studio sessions and on-set downloads, the OWC Mercury Elite Pro mini USB-C with full Thunderbolt 3 compatibility is a powerhouse of data transfer and storage. Choose from 2.5-inch Serial ATA (SATA) hard drive or Solid State Drive (SSD) both with a heat-dissipating, fanless design for cool, super-quiet operation.

The Mercury Elite Pro mini with USB-C delivers up to 540MB/s transfer speeds with up to 4TB storage capacity. Enclosed in sleek, impact resistant brushed aluminum, it's lightweight and compact, so it easily goes where you go.

Key Features
- Up to 4TB storage
- Up to 540MB/s transfer speeds
- Thunderbolt 3 compatible
- Bus powered
- Supported on Mac and PC
- No drivers required
- Ports:
  - (1) USB 3.1 Gen 2 Type-C
  - (1) eSATA 6Gb/s
- Dimensions: 3.8 in (W) x 5.5 in (D) x 1.1 in (H)

# OWC
# Mercury Elite Pro mini with USB-C

## Tech Specs

### Interface
- (1) USB 3.1 Gen 2 Type-C
- (1) eSATA 6 Gb/s

### Drives Supported
- 2.5-inch Serial ATA (SATA) hard drive or Solid State Drive (SSD)

### System Requirements
- Software
  - Operating System
    - Mac: OS X 10.6.8 or later; macOS 10.12 or later
    - PC: Windows 7 or later
    - Other: Linux, Chrome Android and other OSes that support USB 3.1 or later
  - Driver
    - No drivers required
- Hardware
  - Any computer with a USB or eSATA port[1]
- Bootable
  - Mac: OS X 10.6.8 or later; macOS 10.12 or later
  - PC: Booting not supported

### Power Supply
- Bus powered via USB
- USB to DC cable supplied for power when using eSATA
- Optional DC adapter[2] (available as a separate purchase)

### Includes
- OWC Mercury Elite Pro mini
- USB 3.1 Gen 2 (Type-C to Type-C) cable
- USB 3.1 Gen 1 (Type-C to Type-A) cable
- eSATA cable
- DC to USB Type-A connector
- User guide

### Warranty
- Drives included — 3 Year OWC Limited Warranty
- Enclosure only — 1 Year OWC Limited Warranty

### Enclosure Dimensions
- 3.8 in (W) x 1.1 in (H) x 5.5 in (D)
- 9.6 cm (W) x 2.8 cm (H) x 14 cm (D)

### Enclosure Weight (empty)
- 0.7 lb (0.3 kg)

1. For the best performance (10Gb/s) a host with a USB 3.1 Gen 2 port is required

2. DC adapter not required for most applications provided computer bus supplies appropriate power needs.

| PART NUMBER | CAPACITY | UPC | AVAILABLE |
|---|---|---|---|
| OWCMEPMTCES | 0GB | 810586031189 | now |
| OWCME6CM5T01 | 1TB - 5400RPM HDD | 810586031585 | now |
| OWCME6CM5T02 | 2TB - 5400RPM HDD | 810586031592 | now |
| OWCME6CM5T04 | 4TB - 5400RPM HDD | 810586031608 | now |
| OWCME6CM7500 | 500GB - 7200RPM HDD | 810586031615 | now |
| OWCME6CM7T01 | 1TB - 7200RPM HDD | 810586031622 | now |
| OWCME6CM6EP500 | 480GB SSD | 810586031639 | now |
| OWCME6CM6EPT01 | 1TB SSD | 810586031646 | now |
| OWCME6CM6EPT02 | 2TB SSD | 810586031653 | now |